

MG206C-USB, MG166CX-USB, MG166C-USB

Mixing Consoles



MG206C-USB MG166CX-USB MG166C-USB

These versatile analog mixers feature digital bus connectivity for direct digital recording with the supplied Cubase AI4 software.

- 16 or 20 inputs in remarkably lightweight, portable designs.
- The supplied Cubase AI4 software communicates directly with the stereo buses via USB for audio recording and editing, and features a range of MIDI sequencing capabilities, an entire suite of VST effect plug-ins, and a HALion One sample player with selected waves from the famed Yamaha Motif synthesizers.
- Innovative Yamaha one-knob compressor.
- MG166CX-USB features a built-in digital SPX multi-effect processor.
- High-quality Neutrik™ balanced XLR connectors on mono microphone/line channels and XLR-equipped stereo channels.
- Top-mounted input and output connectors for easy setup and re-patching.
- High-performance microphone preamplifiers with switchable phantom power.
- 3-band mid-sweep and high-pass filters.
- Smooth 60-millimeter faders & illuminated channel ON switches.
- Main stereo bus plus two additional stereo group buses and outputs for convenient channel grouping.
- AUX sends with master send controls for convenient processing and monitoring.
- Return level controls for the AUX and STEREO buses.
- Bright meters for visual level monitoring.
- Rack mountable.

OPTIONS

FC5

Foot Switch

for MG166CX-USB



MG206C-USB, MG166CX-USB, MG166C-USB

GENERAL SPECIFICATIONS

	MG206C-USB	MG166CX-USB	MG166C-USB
USB Audio	Input / Output: 44.1 / 48Hz		
Mic/Line inputs	16		10
Line inputs	12 mono + 4 stereo		8 mono + 4 stereo
Mixer input channels	20		16
Group buses	4		4
AUX buses	4		3
Main buses	Stereo		Stereo
Total harmonic distortion (THD+N)	Less than 0.1%, 20Hz-20kHz		
Frequency response	0, +1, -3dB, 20Hz-20kHz		
Hum and noise level	Equivalent input noise (EIN): -128dBu Residual output noise: -98dBu		
Crosstalk (@1kHz)	-70dB		
Power supply adaptor	PA-30 AC adaptor (AC35VCT, 1.4A) 100V, 120V, 220V, 230V or 240V; 50/60Hz		
Power consumption	40W	35W	30W
Dimensions (W x H x D)	478 x 105 [102: MG206C-USB] x 496mm (18.8" x 4.1" [4.0: MG206C-USB] x 19.5") 478 x 105 (102: MG206C-USB) x 496mm		
Net weight	6.0kg (13.2lbs)	5.5kg (12.1lbs)	5.3kg (11.7lbs)

Hum and noise are measured with a 6dB/octave filter @12.7kHz; equivalent to a 20kHz filter with infinite dB/octave attenuation.

INPUT SPECIFICATIONS

Terminal	Gain	Actual Load Impedance	For Use With Nominal	Input Level			Connector
				Sensitivity	Nominal	Max. Before Clip	
MG206C-USB							
CH IN MIC (1-12)	-60dB -16dB	3kΩ	50-600Ω Mics	-80dBu -36dBu	-60dBu -16dBu	-40dBu +4dBu	XLR-3-31 type*
CH IN LINE (1-12)	-34dB +10dB	10kΩ	600Ω Lines	-54dBu -10dBu	-34dBu +10dBu	-14dBu +30dBu	TRS phone jack*
ST CH MIC IN (13/14-19/20)	-60dB -16dB	3kΩ	50-600Ω Mics	-80dBu -36dBu	-60dBu -16dBu	-40dBu -6dBu	XLR-3-31 type*
ST CH LINE IN (13/14, 15/16)	-34dB +10dB	10kΩ	600Ω Lines	-54dBu -10dBu	-34dBu +10dBu	-14dBu +30dBu	Phone jack**
ST CH LINE IN (17/18, 19/20)	-34dB +10dB	10kΩ	600Ω Lines	-54dBu -10dBu	-34dBu +10dBu	-14dBu +30dBu	Phone jack** Phone jack** - RCA pin jack**
CH INSERT IN (1-12)	-	10kΩ	600Ω Lines	-20dBu	0dBu	+20dBu	TRS phone jack**
RETURN [L,R]	-	10kΩ	600Ω Lines	-12dBu	+4dBu	+24dBu	Phone jack**
2TR IN [L,R]	-	10kΩ	600Ω Lines	-26dBV	-10dBV	+10dBV	RCA pin jack**
USB	-	-	-	-	-	-	USB B type
MG166C-USB, MG166CX-USB							
CH IN MIC (1-8)	-60dB -16dB	3kΩ	50-600Ω Mics	-80dBu -36dBu	-60dBu -16dBu	-40dBu +4dBu	XLR-3-31 type*
CH IN LINE (1-8)	-34dB +10dB	10kΩ	600Ω Lines	-54dBu -10dBu	-34dBu +10dBu	-14dBu +30dBu	TRS phone jack*
ST CH MIC IN (9/10, 11/12)	-60dB -16dB	3kΩ	50-600Ω Mics	-80dBu -36dBu	-60dBu -16dBu	-40dBu -6dBu	XLR-3-31 type*
ST CH LINE IN (9/10, 11/12)	-34dB +10dB	10kΩ	600Ω Lines	-54dBu -10dBu	-34dBu +10dBu	-14dBu +30dBu	Phone jack**
ST CH IN (13/14, 15/16)	-	10kΩ	600Ω Lines	-30dBu	-10dBu	+10dBu	Phone jack** RCA pin jack
CH INSERT IN (1-8)	-	10kΩ	600Ω Lines	-20dBu	0dBu	+20dBu	TRS phone jack**
RETURN [L,R]	-	10kΩ	600Ω Lines	-12dBu	+4dBu	+24dBu	Phone jack**
2TR IN [L,R]	-	10kΩ	600Ω Lines	-26dBV	-10dBV	+10dBV	RCA pin jack**
USB	-	-	-	-	-	-	USB B type

Sensitivity is the lowest level that will produce the nominal output level when the unit is set to maximum level.

OUTPUT SPECIFICATIONS

Terminal	Actual Source Impedance	For Use With Nominal	Output Level		Connector
			Nominal	Max. before Clip	
MG206C-USB					
STEREO OUT [L,R]	75Ω	600Ω Lines	+4dBu	+24dBu	XLR 3-32 type* Phone jack*
GROUP OUT [1-4]	150Ω	10kΩ Lines	+4dBu	+20dBu	TRS phone jack***
AUX SEND (1-4)	150Ω	10kΩ Lines	+4dBu	+20dBu	TRS phone jack***
CH INSERT OUT (1-12)	75Ω	10kΩ Lines	0dBu	+20dBu	TRS phone jack**
REC OUT [L, R]	600Ω	10kΩ Lines	-10dBV	+10dBV	RCA pin jack**
MONITOR OUT [L, R]	150Ω	10kΩ Lines	+4dBu	+20dBu	TRS phone jack***
PHONES OUT	100Ω	40kΩ Lines	3mW	75mW	Stereo phone jack**
USB	-	-	-	-	USB B type




*** : Impedance balanced

MG166C-USB, MG166CX-USB					
STEREO OUT [L,R]	75Ω	600Ω Lines	+4dBu	+24dBu	XLR 3-32 type* TRS Phone jack*
GROUP OUT [1-4]	150Ω	10kΩ Lines	+4dBu	+20dBu	TRS Phone jack***
AUX SEND (1-3, EFFECT SEND)	150Ω	10kΩ Lines	+4dBu	+20dBu	TRS Phone jack***
CH INSERT OUT (1-8)	75Ω	10kΩ Lines	0dBu	+20dBu	TRS phone jack**
REC OUT [L, R]	600Ω	10kΩ Lines	-10dBV	+10dBV	RCA pin jack**
MONITOR OUT [L, R]	150Ω	10kΩ Lines	+4dBu	+20dBu	TRS phone jack*
PHONES OUT	100Ω	40kΩ Lines	3mW	75mW	Stereo phone jack**
USB	-	-	-	-	USB B type

*** : Impedance balanced

DIMENSIONS

unit : mm



MG166C, MG166CX, MG206C,
MG166C-USB, MG166CX-USB,
MG206C-USB